

**swela OCEAN**

Material composition	ISO 2076	100% Polyester
Fabric width	EN 1773	≈ 150 cm
Weight	EN 12127	≈ 380 g/m <sup>2</sup>
Piece length		≈ 50 m
Water column	ISO 811	≥ 150 mbar (1500 mm)
Light fastness	ISO 105-B02	≥ 7-8 [of 8]* (≥ 4-5 [of 5]**)
Weather fastness	ISO 105-B04	≥ 7-8 [of 8]* (≥ 4-5 [of 5]**)
Tensile strength	ISO 13934-1	≈ 2700 N <sup>1</sup>   1750 N <sup>2</sup>
Elongation	ISO 13934-1	≈ 30 % <sup>1</sup>   22 % <sup>2</sup>
Colour fastness to rubbing	ISO 105-X12	≥ grade 4-5 <sup>3</sup>   ≥ Note 4-5 <sup>4</sup>
Chlorine resistance	ISO 105-E03	≥ grade 4-5 <sup>3</sup>
Water repellency	AATCC-22	grade 90-100
UV Protection Factor	EN 13758-1	UPF 50+ (mesasured value > UPF 80)
Coating		polyurethan coating
Oeko-Tex-Standard 100		Umweltlabor ACB, Prüf-Nr./ test-no. A96-0071 (Hohenstein HTTI)